

Erratum: "High-efficiency, large-bandwidth silicon-on-insulator grating coupler based on a fully etched photonic crystal structure" [Appl. Phys. Lett. 96, 051126 (2010)]

Liu Liu, Minhao Pu, Kresten Yvind, and Jørn M. Hvam

Citation: *Appl. Phys. Lett.* **97**, 059902 (2010); doi: 10.1063/1.3475767

View online: <http://dx.doi.org/10.1063/1.3475767>

View Table of Contents: <http://apl.aip.org/resource/1/APPLAB/v97/i5>

Published by the [American Institute of Physics](#).

Related Articles

Control of tensile strain in germanium waveguides through silicon nitride layers

Appl. Phys. Lett. **100**, 201104 (2012)

Thickness dependence of the amplified spontaneous emission threshold and operational stability in poly(9,9-dioctylfluorene) active waveguides

J. Appl. Phys. **111**, 093109 (2012)

High quality factor AlN nanocavities embedded in a photonic crystal waveguide

Appl. Phys. Lett. **100**, 191104 (2012)

Double embedded photonic crystals for extraction of guided light in light-emitting diodes

Appl. Phys. Lett. **100**, 171105 (2012)

Nonreciprocal optical Bloch-Zener oscillations in ternary parity-time-symmetric waveguide lattices

Appl. Phys. Lett. **100**, 151913 (2012)

Additional information on *Appl. Phys. Lett.*

Journal Homepage: <http://apl.aip.org/>

Journal Information: http://apl.aip.org/about/about_the_journal

Top downloads: http://apl.aip.org/features/most_downloaded

Information for Authors: <http://apl.aip.org/authors>

ADVERTISEMENT



Goodfellow
metals • ceramics • polymers • composites
70,000 products
450 different materials
small quantities fast

www.goodfellowusa.com

Erratum: “High-efficiency, large-bandwidth silicon-on-insulator grating coupler based on a fully etched photonic crystal structure” [Appl. Phys. Lett. 96, 051126 (2010)]

Liu Liu (刘柳),^{a)} Minhao Pu (蒲敏皓), Kresten Yvind, and Jørn M. Hvam
*Department of Photonics Engineering, DTU-Fotonik, Technical University of Denmark,
Ørstedes Plads Bldg. 343, 2800 Kgs. Lyngby, Denmark*

(Received 14 July 2010; accepted 16 July 2010; published online 2 August 2010)

[doi:10.1063/1.3475767]

It has come to our attention that one more reference, i.e., Ref. 15, should be added. In it, the idea of using fully etched subwavelength structures in a grating coupler was first proposed, considering transverse magnetic polarized light. The idea and structure were later employed, improved, and realized experimentally in Ref. 12 for transverse electrical polar-

ized light, which is more relevant to the present letter, and was referred to originally. Nevertheless, Ref. 15 should be added accompanying Ref. 12 in suitable locations. We apologize for the unfortunate oversight.

¹⁵R. Halir, P. Cheben, S. Janz, D.-X. Xu, Í. Molina-Fernández, and J. G. Wangüemert-Pérez, *Opt. Lett.* **34**, 1408 (2009).

^{a)}Electronic mail: lliu@fotonik.dtu.dk.